

GENERATOR SET SPECIFICATIONS

- * High quality and reliability.
- * Structurally easy start-up and maintenance.
- * Heavy duty water cooled diesel engine.
- * Brushless industrial alternator with AVR.
- * Steel base frame integrated with high cap. fuel tank.
- * Anti - vibration mounts.
- * High temperature, low oil pressure, fuel level alarms and shutdowns.
- * Engine filled with lubrication oil and coolant mix.
- * Engine coolant heater.
- * Fuel level indicator on LCD display of controller.
- * Complete protection of rotating and hot parts.
- * Industrial type silencer.
- * Fuel tank and engine oil heater (Option).

CONTROL PANEL



- * Multi - lingual control panel with microprocessor.
- * Digital LCD - display provides simple, intuitive menu navigation and control of generator set operation.
- * Key information is displayed via the LCD screen.
- * Simple push-button control;
OFF - MANUAL - AUTO - TEST - START
- * Manual programming on control panel.
- * Circuit Breaker.
- * Emergency stop button, light and sound alarm siren.
- * Battery charger.
- * Remote control with GSM modem (option).

SOUNDPROOF CANOPY



- * Sound attenuated.
- * Robust and highly corrosion resistant construction.
- * Excellent access for maintenance through 2-6 doors.
- * Fully weatherproof.
- * Base mounted lifting eyes and canopy lifting points.
- * Non-flammable acoustic foam.
- * Totally enclosed exhaust silencing system.
- * Vibration absorber pads.

Manufacturer reserves the right to make changes in generator set specifications without prior notice.

www.ett.com.tr

OUTPUT RATINGS

Standby Power (ESP)	kVA / kW	850 / 680
Prime Power (PRP)	kVA / kW	773 / 618
Current (ESP)	A	1227
Voltage - Frequency	V - Hz	400 / 230 - 50
Phase Quantity - Power Factor	Unit - Cosφ	3 - 0,8

ENGINE

Engine Make & Model	C.SDEC	JS12V720TAD
Engine Mechanical Prime Power	kW / (HP)	720 / 965
Air Intake System		Turbocharger & AC
Cylinder Volume	L	28,3
Cylinder Quantity / Type		12 / V
Bore & Stroke	MM x MM	138 x 158
Compression Ratio		16:1
Governing Type		Electronic
Engine Speed	RPM	1500
Cooling Method		Water
Cooling System Capacity	L	84
Oil Lubrication System Capacity	L	58
Electrical System	V DC	24
Fuel Consumption		
100 % Prime load	L / H	154,5
75 % Prime load	L / H	115,9
50 % Prime load	L / H	77,3
Fuel tank Capacity	L	1500

ALTERNATOR

Alternator Make & Model	C.STAMFORD	
Alternator Type	Electronic (AVR)	
Standby Power (ESP)	kVA	Brushless
Voltage - Frequency	V - Hz	850
Voltage Regulation		400 / 230 - 50
Insulation / Protection Class		+/- 1.0
Pole Quantity		H / IP 21
		4

DIMENSIONS AND WEIGHTS



Open Type	LxWxH - M / Weight - KG	4 x 1,7 x 2,3 / 5400
Canopied Type	LxWxH - M / Weight - KG	5 x 2 x 2,6 / 6200

Standby Power (ESP): Emergency power under varying electrical load. Overload is not permitted.

Prime Power (PRP): Nominal power under varying electrical load for unlimited hours. 10 % overload is available for a period of 1 hour within 12 hours.

Electrotech Dış Ticaret ve Tekstil Limited Sirketi Istanbul Trakya Serbest Bolge Subesi, Atatürk Bulvarı, Erguvan Sokak No: 8/1, Catalca / Istanbul / TURKEY

Tel:+90 212 4383825-4383856, Gsm:+90 532 5446730, cagrio@electrotech-trade.com